


0210 系列



型号	P0210-W001	P0210-W002	P0210-W003	P0210-W004	P0210-W005	P0210-Wx01*
订货号	4011.0210.1020	4011.0210.2129	4011.0210.3045	4011.0210.4560	4011.0210.6191	4011.0210.xxxx**
起订量	块	1	1	1	1	2
适用激光	-	Excimer, UV, harmonics of Nd:YAG (266nm, 355nm), Diode, Ruby				
材料	-	特殊塑料				
颜色	-	绿色				
防护等级	-	180 – 315 D AB5+IR AB3 (OD 10+) > 690 – 700 D AB5 (OD 6+) > 315 – 360 DIR AB5 (OD 9+) > 700 – 750 D AB5 (OD 7+) > 360 – 370 DIR AB5 (OD 7+) > 750 – 800 D AB5 (OD 6+) > 370 – 400 DIR AB5 (OD 6+) > 800 – 850 D AB5 (OD 5+) > 400 – 425 DIR AB5 (OD 5+) > 850 – 1070 D AB5 (OD 6+) > 425 – 440 DIR AB4 (OD 4+) > 1070 – 1080 D AB5 (OD 5+) > 440 – 447 DIR AB3 (OD 3+) > 1080 – 1090 D AB4 (OD 4+) > 447 – 454 DIR AB2 (OD 2+) > 1090 – 1105 D AB3 (OD 3+) > 454 – 465 DIR AB1 (OD 1+) > 1105 – 1120 D AB2 (OD 2+) > 600 – 635 D AB1 (OD 1+) > 1120 – 1160 D AB1 (OD 1+) > 635 – 655 D AB2 (OD 2+) > 655 – 670 D AB3 (OD 3+) > 670 – 680 D AB4 (OD 4+) > 680 – 690 D AB5 (OD 5+)				
VLT (约)	%	21.5				
厚度 (约)	mm	3.8				
尺寸 (约)	mm	100 x 200	210 x 297	300 x 450	450 x 600	610 x 915 待定义
尺寸误差	mm	±0.5				
安全认证	-	EN 12254, PF CE				

* “Wx01” 为非标型号的编号, 依次为 Wx01, Wx02, Wx03...。

** 最大尺寸可大于 610 x 915mm; 非标尺寸或不规则形状, 客户可提供图纸定制, 订货前与供应商确认。

ULT

ALSIDENT

REVEN

PROTECT

KENTEK

ELEN

PPE

Acc

New